

































Budget Active Monitors Comparison

													
	Truth B3031A	Truth B3030A	Truth B2031A	Truth B2030A	Truth B2092A	Truth B1030A	Rokit RP-8	Rokit RP-6	Rokit RP-5	Rokit RP-10S	KRK 10S	Diamond Studio 8.2 ProActive	Diamond Studio 8.1 ProActive
													
Inputs/Outputs	Balanced XLR/Jack	Balanced XLR/Jack	Balanced XLR/Jack	Balanced XLR/Jack	Balanced XLR	RCA & Balanced XLR/Jack	RCA & Balanced XLR/Jack	RCA & Balanced XLR/Jack	RCA & Balanced XLR/Jack	RCA & Balanced XLR/Jack	RCA & Balanced XLR/Jack	RCA & Balanced XLR/Jack	RCA & Balanced XLR/Jack
Driver (*)	8 1/4 LF; 2 HF Ribbon	6 1/4 LF; 2 HF Ribbon	8 1/4 LF; 1 HF	6 1/4 LF; 1 HF	2 x 8	5 1/4 LF; 1 HF	8 LF; 1 HF	6 LF; 1 HF	5 LF; 1 HF	10	10	6 1/4 LF; 1 HF	5 LF; 1 HF
Frequency Response	50Hz – 24kHz,	50Hz – 24kHz,	50Hz – 21kHz,	50Hz – 21kHz,	32Hz – 80Hz, ±3 dB	50Hz – 20kHz,	44Hz – 20kHz, ±1.5 dB	48Hz – 20kHz, ±1.5 dB	52Hz – 20kHz, ±2 dB	36Hz – 50Hz, ±1.5 dB	34Hz – 50Hz – 130Hz, variable, ±1.5 dB	45Hz – 24kHz, ±3 dB	50Hz – 24kHz, ±3 dB
Power Rating	100W RMS @4Ω - LF Driver 30W RMS @6Ω - HF Driver	50W RMS @4Ω - LF Driver 25W RMS @6Ω - HF Driver	80W RMS @4Ω - LF Driver 25W RMS @4Ω - HF Driver	80W RMS @4Ω - LF Driver 20W RMS @6Ω - HF Driver	360W Peak @8Ω	35W RMS @4Ω - LF Driver 15W RMS @6Ω - HF Driver	70W - LF Driver 20W - HF Driver	50W - LF Driver 18W - HF Driver	30W - LF Driver 15W - HF Driver	150W RMS	150W RMS	60W @4Ω - LF Driver 40W @4Ω - HF Driver	60W @4Ω - LF Driver 40W @4Ω - HF Driver
Sensitivity (SPL)	116dB SPL @ 1m max	113dB SPL @ 1m max	116dB SPL @ 1m max	113dB SPL @ 1m max	117dB SPL @ 1m max	110dB SPL @ 1m max					113dB Peak	108dB SPL @ 1m max	106dB SPL @ 1m max
Dimensions (mm) (H x W x D)	400 x 250 x 290	315 x 215 x 210	400 x 250 x 290	317 x 214 x 211	620 x 325 x 582	288 x 198 x 280	394 x 275 x 299	330 x 225 x 273	282 x 185 x 230	382 x 355 x 398	382 x 355 x 408	364 x 212 x 322	295 x 198 x 280
Weight (kg)	15	10	15	9.84	33.1	5.5	11.7	8.75	6	19.05	18.24	8	7.5
RRP* (incl. VAT)	R 8,299	R 6,999	R 7,399.00	R 6,299.00		R 3,999.00	R 9,499.00	R 7,299.00	R 5,499.00	R 5,299.00	R 6,999.00	R 6,495	R 4,895
Website	Link	Link	Link	Link	Link	Link	Link	Link	Link	Link	Link	Link	Link

												
	Rubicon R8A	Rubicon R6A	Rubicon R5A	Rubicon R10S	Resolv 80A	Resolv 65A	Resolv 50A	Resolv Sub88	Resolv 120a	M1 Active MKII	M1 Active 620	M1 Active 520
												
Inputs/Outputs	RCA & Balanced XLR/Jack	RCA & Balanced XLR/Jack	RCA & Balanced XLR/Jack	RCA & Balanced XLR	RCA & Balanced XLR/Jack	RCA & Balanced XLR/Jack	RCA & Balanced Jack	RCA & Balanced XLR	RCA & Push Terminals	Balanced XLR/Jack	Balanced XLR/Jack	Balanced XLR/Jack
Driver (*)	8 LF; 2 HF Ribbon	6 1/4 LF; 2 HF Ribbon	5 LF; 2 HF Ribbon	10	8 LF; 1 HF	6 1/4 LF; 1 HF	5 1/4 LF; 1 HF	8	10	6 1/4 LF; 1 HF	6 1/4 LF; 1 HF	5 LF; 1 HF
Frequency Response	40Hz – 27kHz, ±3 dB	57Hz – 27kHz, ±3 dB	58Hz – 27kHz, ±3 dB	20Hz – 200Hz, ±3 dB	58Hz – 20kHz, ±3 dB	62Hz – 25kHz, ±3 dB	63Hz – 26kHz, ±3 dB	20Hz – 150Hz, ±3 dB	30Hz – 300Hz, ±3 dB	50Hz – 20kHz, ±2 dB	49Hz – 20kHz,	56Hz – 20kHz,
Power Rating	75W RMS - LF Driver 25W RMS - HF Driver	75W RMS - LF Driver 25W RMS - HF Driver	50W RMS - LF Driver 25W RMS - HF Driver	150W RMS	75W RMS - LF Driver 25W RMS - HF Driver	75W RMS - LF Driver 25W RMS - HF Driver	50W RMS - LF Driver 20W RMS - HF Driver	80W RMS	120W RMS	75W @6Ω - LF Driver 25W @4Ω - HF Driver	65W - LF Driver 30W - HF Driver	50W - LF Driver 25W - HF Driver
Sensitivity (SPL)					97dB SPL @ 1W/1m	97dB SPL @ 1W/1m	97dB SPL @ 1W/1m	94dB SPL @ 1W/1m	94dB SPL @ 1W/1m	118dB SPL @ 1m max	90dB SPL @ 1m max	90dB SPL @ 1m max
Dimensions (mm) (H x W x D)	437 x 284 x 305	381 x 235 x 273	337 x 203 x 235	406 x 324 x 343	407 x 283 x 330	346 x 216 x 254	305 x 203 x 223	347 x 312 x 312	432 x 356 x 413	381 x 216 x 253	380 x 216 x 260	267 x 165 x 197
Weight (kg)	12	8.2	7.3	13.8	11.4	8.2	6.9	10	7.75	8.9	9.6	6
RRP* (incl. VAT)	R 8,995	R 8,495	R 6,795	R 6,495	R 6,795	R 5,795	R 4,895	R 2,495	R 3,495	R 5,495	R 6,495	R 4,795
Website	Link	Link	Link	Link	Link	Link	Link	Link	Link	Link	Link	Link

*RRP: Recommended Retail Price updated 07/07/09

blue cow //budget monitor comparison

e-mail: info@bluecow.co.za

tel: +27 (0)21 883 8602

www.bluecow.co.za

Equipment specifications are subject to change. This is not a quotation, prices are for comparison purposes only. Contact Blue Cow for latest pricing and specification updates